AS5214 Ultra Low Jitter LVCMOS VCTCXO

Description

The AS5214 is a voltage-controlled temperature-compensated crystal oscillator (VCTCXO) that provides an LVCMOS output clock from 10 MHz to 76.8 MHz. Digital temperature sensing and frequency compensation maintain a stable reference clock, while the voltage-control input enables smooth frequency adjustment around the factory-programmed nominal frequency.

The tuning slope is programmable for the required application, with a maximum slope of 6 ppm/V. The center control voltage and frequency pull range are factory configured through the device ordering code. The AS5214 operates from a wide 1.8 V to 3.3 V supply range, and its on-chip LDO provides robust power supply noise rejection, simplifying external supply filtering.

The AS5214 is available in industry-standard 2520, 3225, and 5032 packages with industrial, extended industrial, and automotive device grades. Its wide operating range, low-jitter output, and programmable voltage control support precision timing in GNSS receivers, microwave backhaul, narrow-band communications, storage platforms, servers, and test and measurement instruments.



Key Features

- Frequency range: 10 to 76.8 MHz
- Standard LVCMOS output
- Ultra-low jitter: 93 fs Typ RMS
  (12 kHz – 20 MHz, @76.8 MHz)
- Operating temperature range:
  - -40 to 85 ℃ (Industial grade)
  - -40 to 105 ℃ (Extended-Industial grade)
  - -40 to 105 ℃ (AEC-Q100 grade 2)
- Temperature stability:
  - ±0.5 ppm (Grade C)
  - ±20 ppm (Grade D)
- Programmable tuning slope up to 6 ppm/V
- Integrated LDO for on-chip power supply noise filtering
- Support 1.8V, 2.5V, 3.3V V_{DD} supply operation
- Standard DFN 2520, 3225 and 5032 packages

Application

- Precision GNSS systems
- Microwave backhaul
- Narrow-band communications
- Storage and servers
- Test and measurements

Pin definition



Top view

Pin#	Description
1	VC = Voltage control input
2	NC = Not connect
3	GND = Ground
4	NC = Not connect
5	CLK = Clock output
6	VDD = Power supply

1. Ordering Guide

XO Series	Description
5214	Voltage Control

	Device Type
A	General
B	Factory defined setting

	Temperature Stability Grade
S	+/- 5ppm
D[1]	+/- 20ppm

	Device Grade	Temperature Grade
I	Industrial grade	-40 to 85°C
E[2]	Extended industrial grade	-40 to 105°C
A[2]	Automotive grade	-40 to 105°C



	Power Supply
A	3.3 V
B	2.5 V
C	1.8 V

Configuration Code[3]	Description
xxxxx	Five digit numeric code

The chip supports user-defined tuning slope and power supply voltage.
A unique five digit numeric code will be assigned for the specific combination of settings.

Device Revision

	Package
A	5032
B	3225
C	2520

Code	Packing type	Qty
T	7-inch reel	250
R	13-inch reel	2500
F	13-inch reel	5000
<blank>	Bulk	Sample

Note:

1. Temperature compensation is not applied for grade-D device. Frequency is calibrated at 25 ℃ in production test.
2. Contact Aeonsemi for extended-industrial and automotive-grade devices.
3. The five-digit numeric code is an identification of the configurations. Check the datasheet appendix for the details.

2. Electrical Specifications

Table 2.1. Electrical Specifications

Parameter	Symbol	Min	Typ	Max	Unit	Note
Operating Temperature Range						
Temperature Range	T_A	-40	–	85	℃	Industrial grade
		-40	–	105	℃	Extended industrial grade
		-40	–	105	℃	Automotive AEC-Q100 Grade2
Supply Voltage and Power Consumption						
Supply Voltage	V_{DD}	1.62	–	3.63	V	Core voltage
Supply Current (F_{CLK} = 38.4 MHz)	I_{CORE}	–	4	5	mA	Tristate Hi-Z (Output disabled)
	I_{DRV}	–	6	8	mA	1.8V LVCMOS (C_L=15pF)
		–	8	10	mA	2.5V LVCMOS (C_L=15pF)
		–	10	13	mA	3.3V LVCMOS (C_L=15pF)
Frequency Range						
Frequency Range	F_{CLK}	10	–	76.8	MHz	Standard frequency options
		10, 16, 19.2, 20, 25, 26, 32, 38.4, 50, 52				Contact Aeonsemi for other frequency options
Frequency Tolerance						
Initial frequency accuracy[1]	F_{INIT}	-2	–	2	ppm	Grade C
		-5	–	5	ppm	Grade D
Temperature stability over full temp range[2]	F_{STAB}	-0.5	–	0.5	ppm	Grade C
		-20	–	20	ppm	Grade D
Aging	S_{AGING}	-1	–	1	ppm/y	Maximum aging slope at 25 ℃
	F_{AGING}	-3	–	3	ppm	10-year aging at 25℃
Notes: 1. Inclusive of initial frequency tolerance at 25℃, variations over supply voltage, load and humidity after 2 times of reflows. 2. Frequency / temperature characteristics with offset removed.						
VCXO Control Characteristics						
Control voltage input	V_C	0	–	V_{DD}	V	Input reference voltage range
Center control voltage[3]	V_{CEN}	–	$V_{DD}/2$	–	V	Factory-programmable center voltage
Tuning slope[3]	K_V	–	–	6	ppm/V	Factory-programmable tuning slope
Control voltage linearity	Lin	-3	–	3	%	Linearity error
Notes: 3. The center control voltage and tuning slope are factory-programmable to meet application-specific requirements. Contact aeonsemi.com/contact_us to obtain the unique part number for the required configuration.						

Continued on next page

Parameter	Symbol	Min	Typ	Max	Unit	Note
Output Characteristics						
Powerup time	T_{OSC}	–	–	4	ms	Time from power reaches 0.9 × V_{DD} to output frequency (F_{CLK}) within spec
Duty cycle	DC	45	–	55	%	LVCMOS (C_L=15pF)
Rise/Fall time (20% to 80% VPP)	$T_{R/F}$	–	0.5	1.5	ns	LVCMOS (C_L=15pF)
LVCMOS	V_{OH}	0.83×V_{DD}	–	–	V	C_L=15pF
	V_{OL}	–	–	0.17×V_{DD}	V	
Phase Noise and Jitter						
RMS jitter	R_J	–	100	200	fs	F_{CLK} >= 50 MHz
BW: 12k - 20MHz		–	150	300	fs	F_{CLK} <50 MHz
Phase noise	PN_{10}	–	-89	–	dBc/Hz	Phase noise at 10Hz offset
38.4MHz LVCMOS output	PN_{100}	–	-119	–	dBc/Hz	Phase noise at 100Hz offset
V_{DD} = 1.8 - 3.3V	PN_{1k}	–	-143	–	dBc/Hz	Phase noise at 1kHz offset
	PN_{10k}	–	-152	–	dBc/Hz	Phase noise at 10kHz offset
	PN_{100k}	–	-158	–	dBc/Hz	Phase noise at 100kHz offset
	PN_{1M}	–	-162	–	dBc/Hz	Phase noise at 1MHz offset
	PN_{10M}	–	-163	–	dBc/Hz	Phase noise at 10MHz offset
PSNR						
Spurs from power noise	PSNR	–	-76	–	dBc	100 kHz sine wave
50mV ripple		–	-75	–	dBc	200 kHz sine wave
V_{DD} = 1.8V		–	-75	–	dBc	500 kHz sine wave
		–	-75	–	dBc	1 MHz sine wave
Spurs from power noise	PSNR	–	-83	–	dBc	100 kHz sine wave
50mV ripple		–	-83	–	dBc	200 kHz sine wave
V_{DD} = 2.5 or 3.3V		–	-83	–	dBc	500 kHz sine wave
		–	-82	–	dBc	1 MHz sine wave

Table 2.2. Environmental Compliance and Package Information

Parameter	Value
Moisture sensitivity level (MSL)	3

Notes:

For additional product information not listed in the data sheet (e.g. RoHS Certifications, MSDS data, qualification data, REACH Declarations, ECCN codes, etc.), contact aeonsemi.com/contact_us

Table 2.3. Absolute Maximum Ratings[1]

Parameter	Symbol	Rating	Unit
Maximum operating temperature	T_{AMAX}	125	℃
Storage temperature	T_S	-55 - 125	℃
Supply voltage	V_{DD_MAX}	-0.5 - 3.8	V
Input voltage	V_{IN_MAX}	-0.5 - V_{DD}+0.3	V
ESD HBM (JESD22-A114)	HBM	4.0	kV
ESD CDM (JESD22-C101)	CDM	1.0	kV
Solder Temperature[2]	T_{PEAK}	260	℃
Solder time at T_{PEAK}[2]	T_P	20 - 40	sec

Notes:

1. Stresses beyond those listed in this table may cause permanent damage to the device. Functional operation specification compliance is not implied at these conditions. Exposure to maximum rating conditions for extended periods may affect device reliability.
2. The device is compliant with JEDEC J-STD-020.

3. Package Outline Drawing

Figure 3.1. shows the package outline drawing for the AS5214 devices. Details of dimension for different size options are listed in Table 3.1.



Figure 3.1. Package Outline Drawing

Table 3.1. Dimensions of Package Outline Drawing (mm)

Symbol	5032 Package	3225 Package	2520 Package
A	1.146 ± 0.100	1.146 ± 0.100	0.876 ± 0.100
b	0.640 ± 0.050	0.600 ± 0.050	0.380 ± 0.050
b1	0.640 ± 0.050	0.600 ± 0.050	0.380 ± 0.050
D	3.200 ± 0.100	2.500 ± 0.050	2.000 ± 0.050
e	1.270 BSC	1.100 BSC	0.900 BSC
E	5.000 ± 0.100	3.200 ± 0.050	2.500 ± 0.050
L	0.900 ± 0.075	0.700 ± 0.075	0.550 ± 0.075
L1	0.100 ± 0.075	0.100 ± 0.075	0.100 ± 0.075
L2	0.910 ± 0.075	0.200 ± 0.075	0.160 ± 0.075

4. Recommended PCB Land Pattern

Figure 4.1. shows the drawing of recommended PCB land pattern for the AS5214 devices. Details of dimension for different size options are listed in Table 4.1.



Figure 4.1. Recommended PCB Land Pattern

Table 4.1. Dimensions of Recommended PCB Land Pattern (mm)

Symbol	5032 Package	3225 Package	2520 Package
D1	2.20	1.70	1.35
E1	1.27	1.10	0.90
X1	1.20	1.00	0.85
Y1	0.84	0.80	0.58
Y2	0.84	0.80	0.58

Notes:

The following notes and stencil design are shared as recommendations only. A customer or user may find it necessary to use different parameters and fine-tune their SMT process as required for their application and tooling.

General

1. All dimensions shown are in millimeters (mm) unless otherwise noted.
2. Dimensioning and Tolerancing is per the ANSI Y14.5M-1994 specification.
3. This Land Pattern Design is based on the IPC-7351 guidelines.
4. All dimensions shown are at Maximum Material Condition (MMC). Least Material Condition (LMC) is calculated based on a Fabrication Allowance of 0.05 mm.

Solder Mask Design

1. All metal pads are to be non-solder mask defined (NSMD). Clearance between the solder mask and the metal pad is to be 60 µm minimum, all the way around the pad.

Stencil Design

1. A stainless steel, laser-cut and electro-polished stencil with trapezoidal walls should be used to assure good solder paste release.
2. The stencil thickness should be 0.125 mm (5 mils).
3. The ratio of stencil aperture to land pad size should be 0.8 1 for the pads.

Card Assembly

1. A No-Clean, Type-3 solder paste is recommended.
2. The recommended card reflow profile is per the JEDEC/IPC J-STD-020 specification for Small Body Components.

5. Top Mark

Figure 5.1. shows the top mark specifications for the AS5214 devices. Description of each line is listed in Table 5.1.



Figure 5.1. Top Mark

Table 5.1. Top Mark Description

Line	Position	Description
1	1-5	Device Name
2	1-5	Unique 5-digit Device Configuration Number
3	1	Pin 1 orientation mark (dot)
	2-3	Year (last two digits of the year), to be assigned by assembly site (ex: 2025 = 25)
	4-5	Calendar Work Week number (1-53), to be assigned by assembly site
	6	Manufacturer code

6. Packing Specification

Figure 6.1. shows the packing specifications for the AS5214 devices. Details of the tape specifications are listed in Table 6.1.
.



Figure 6.1. Tape Specification

Table 6.1. Dimensions of Tape (mm)

Symbol	5032 Package	3225 Package	2520 Package
A0	3.50 ± 0.10	2.80 ± 0.10	2.30 ± 0.10
B0	4.30 ± 0.10	3.50 ± 0.10	2.80 ± 0.10
K0	1.25 ± 0.10	1.05 ± 0.10	1.30 ± 0.10
E1	1.75 ± 0.10	1.75 ± 0.10	1.75 ± 0.10
F	5.50 ± 0.05	5.50 ± 0.05	5.50 ± 0.10
W	12.00 ± 0.30	12.00 ± 0.30	12.00 (+0.30/-0.10)
T	0.30 ± 0.05	0.30 ± 0.05	0.30 ± 0.05
P0	4.00 ± 0.10	4.00 ± 0.10	4.00 ± 0.10
P1	8.00 ± 0.10	8.00 ± 0.10	8.00 ± 0.10
P2	2.00 ± 0.05	2.00 ± 0.05	2.00 ± 0.10
ϕD0	1.50 ± 0.10	1.50 ± 0.10	1.50 (+0.10/-0)
ϕD1	1.60 ± 0.10	1.60 ± 0.10	1.05 ± 0.10

7. Important Notice and Disclaimer

Aeonsemi provides technical information such as datasheets, characterization reports, application notes, reference designs, and other resources “as is” and with all faults, and disclaims all warranties, express and implied, including without limitation any implied warranties of merchantability, fitness for a particular purpose or non-infringement of third-party intellectual property rights. These resources are subject to change without notice except when PCN is applicable. Aeonsemi grants you permission to use these resources only for development of an application that uses the Aeonsemi products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other Aeonsemi intellectual property right or to any third-party intellectual property right. Aeonsemi disclaims responsibility for, and you will fully indemnify Aeonsemi and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

Aeonsemi’s products are provided subject to Aeonsemi’s Terms of Sale (aeonsemi.com/terms) or other applicable terms available either on aeonsemi.com or provided in conjunction with such Aeonsemi products.

Contact: marketing@aeonsemi.com

8. Revision History

Revision	Date	Description
1.06	Oct 2026	Updated ordering guide
1.05	Aug 2026	Removed paragraph first-line indentation Corrected top mark position table
1.03	Mar 2026	Updated the Top Mark Rule
1.02	Sep 2025	Corrected several description errors
1.01	Aug 2025	Officially release as mass production version
0.09	Feb 2025	Added frequency options; ”2520” package outline diagram
0.08	Aug 2024	Added ”5032” & ”3225” package outline diagram
0.07	Apr 2024	Added ”2520” package option
0.06	Feb 2024	Updated the ”Ordering guide”
0.05	Aug 2023	Revised the stability for D-grade option
0.04	Jul 2023	Updated the package outline
0.03	Jun 2023	Updated the ”Ordering guide” and added phase noise jitter for clock >=100 MHz
0.02	Feb 2023	Updated the ”Temperature Stability Grade” D grade
0.01	Nov 2021	Preliminary release